



RT500 Ramp Trailer Specifications AU



THE TRAILER YOUR CAR WOULD CHOOSE

| | |
|---------------------------------|------------------------------------|
| DECK LENGTH 5000mm | DECK WIDTH 2000mm |
| OVERALL LENGTH 6500mm | OVERALL WIDTH 2550mm |
| FENDER HEIGHT 180mm | GROUND CLEARANCE 385mm |
| G.V.W.R. 2500kg | G.A.W.R. 1700kg |
| TARE WEIGHT 500kg | LOAD CAPACITY 2000kg |
| DECK ANGLE 10-degrees | FLARED TAIL WIDTH 2195mm |

ENGINEERED TO BE EFFORTLESS

| | |
|---|--|
| FENDERS Removable for extra door clearance | LICENCE PLATE BRACKET Aluminium, fold up |
| TIEPOINTS Continuous airline track and slotted chassis rail | COUPLING 1 7/8 Snap-on steel coupler |
| JACK Centre mount jockey wheel, auto stow wheel | TYRES 175 R13 8 PLY Light Truck |

| | |
|--|---|
| WHEELS 13" Shiftr Alloy | SUSPENSION Independent torsion arm (PU) |
| AXLE (patented) 1700kg galvanised steel torsion | BRAKES 10" electric |
| HUBS 1700kg | ELECTRIC CONNECTOR 7-Way RV, flat pin trailer plug |
| LIGHTING Micro LED fender mounted clearance Recessed LED stop, tail, indicators Combined LED/reflector marker lights | |
| BUILT TO LAST A LIFETIME | |
| FINISH-ALUMINIUM PARTS Silver anodising and black powder coating | FINISH-STEEL PARTS Hot dip galvanised |
| CHASSIS & TONGUE Extruded aluminium 6005-T6 Extruded 6005-T6 C section | DECK Extruded aluminium 6005-T6 interlocking panels |